

Technical Rider Wim Sonneveld hall



Contact

Stagedoor + mailing adress	Leidsekade 91 1017 PN Amsterdam
Loading dock	Marnixstraat 402 1017 PL Amsterdam
Phonenumber	020 5552627
Head of technical department	Melvin Oerlemans 020 5552660 melvin.oerlemans@delamar.nl
Deputy head of technical department	Mark Bouma mark.bouma@delamar.nl

Logistics

Loading dock adress	Marnixstraat 402
Minimum passage towards the stage	2.35 m x 2.74 m (w x h)
Maximum # trucks docked simultaneously	1
Details	Dock is shared for both venues. No parking allowed in the loading dock.

Seating

Seats	949
Stalls	569
Balcony	380
Show start	20.00



Stage

Stage Dimensions

Stageplot: 15 m x 10.68 m

Width

Left wall	-11,01 m
Right wall	10,5 m
Sidebrige left	-8,08 m
Sidebrige right	8,12 m
Proscenium opening	11,94 m
Downstage proscenium max.	14,31 m (L -7,79, R 6,52)
Downstage proscenium min.	8,96 m (L -4,48, R 4,48)
Orchestra pit	14,52 m

Depth measured from plotting line

Rearside proscenium	-2,03 m
Downstage edge	-3,3 m
Lighting bridge (mid)	-10 m
Edge of audit balcony (mid)	-10,88 m
Audit rear wall	-21 m
Rear fly bar (#46)	10,44 m
Rear stagebridge	10,68 m
Rearwall stage	10,81 m



Height

Grid	15,1 m
Max. flybar height	13,75 m
Max. poscenum height	6,75 m
Min. Proscenium height	0,5 m
Proscenium height	7,02 m
Under left gallery	5,34 m (underside air duckting)
Under right gallery	7,85 m
Under rear gallery	7,85 m
Stageheight	0,95 m

Flooring

Wooden floor	Keruing parquet
Rake	None
Marley	Available in black
Max load (kg/m2)	500

Curtain

Colour	Red
Operation	Greek, manually operated stage right

Stage bordering

Legs, borders, gauss and backdrops available. Contact the venue for details.



Flybars	
Manufacturer	STS (Silicon Theatre Scenery)
Operator location	Stage right
Regular bars	
Bar numbers	1 through 40
Spacing	0,20 m
Bar width	15 m
Max height	13.75 m
Max load	500 kg
Max speed	1.8 m/s
Rear bars	
Bar numbers	41 t/m 46
Spacing	0,40 m
Bar width	15 m at bar 41, 12,75 at bar 46; asymmetrical
Max height	13,75 m
Max load	500 kg
Max speed	1 m/s
Side flybars	1 on stage left, 1 on stage right. Max load: 500kg

Single point hoists	
Hoists:	6 to be placed at will on the grid above stage
Max load	250 kg
Max speed	1.8 m/s

Chain hoists	
Position	4 in traverses above stage
Max load	1000 kg
Max speed	0,8 m/s